




coflex CA

Conceived to subdivide large tile bays, COFLEX CA movement joints in co-extruded synthetic resin are composed of rigid, perforated anchoring flanges and a durable, soft upper surface which is resistant to mildew, bacteria, weathering, corrosion, wear and UV rays. Suitable for indoor and outdoor applications; the profile section provides limited protection to the tile edge. Ideally used in retail shops, hotels, sports facilities and schools.



CA100P23

Length: 2,70 meters



Coextruded Synthetic
Resinil + Resinflex


B = 10 mm



Coextruded Synthetic Resinil + Resinflex



coflex >> CA Co-extruded Synthetic Resinil + Resinflex			
Item	H mm	Finish	pcs
CA60P11270	6	P11 - Pure White	72*
CA80P11270	8	P11 - Pure White	64*
CA100P11270	10	P11 - Pure White	56*
CA125P11270	12,5	P11 - Pure White	48*
CA60P23270	6	P23 - Cement Grey	72*
CA80P23270	8	P23 - Cement Grey	64*
CA100P23270	10	P23 - Cement Grey	56*
CA125P23270	12,5	P23 - Cement Grey	48*
CA150P23270	15	P23 - Cement Grey	40*
CA200P23270	20	P23 - Cement Grey	32*
CA60P32270	6	P32 - Dark Beige	72*
CA80P32270	8	P32 - Dark Beige	64*
CA100P32270	10	P32 - Dark Beige	56*
CA125P32270	12,5	P32 - Dark Beige	48*
CA60P51270	6	P51 - Black	72*
CA80P51270	8	P51 - Black	64*
CA100P51270	10	P51 - Black	56*
CA125P51270	12,5	P51 - Black	48*



* 10% increase for quantities lower than 20.

** 10% increase for quantities lower than those indicated.