


coflex CBR

COFLEX CBR is composed of a twin double metal profile to host the internal rubber seal. This product has been designed to ensure a certain grade of protection to the tile and relative work load it may have to bear. The synthetic rubber insert efficiently compensates and absorbs flooring movements along with the covering material. COFLEX CBR is suitable to bear distributed weights and tensions. Select a joint with the height matching exactly the tile thickness, the joint must not rise above the level of covering surface but should be laid 0,5 ÷ 1 mm below the edge of the tiles. Typical flooring areas: retail shops, hotels, sporting centers and schools.




CBR100AN23

Length: 2,70 meters - Insert assembled.




Natural Aluminum +
Synthetic Insert

B = 10,2 mm



Synthetic Insert

B = 5 mm



Natural Aluminium + Synthetic insert



AN

P23

P51

coflex >> CBR in Natural Aluminum + Synthetic Insert				
Item	H mm	Finish		pcs
CBR45AN23270	4,5	A23 - Cement Grey		30*
CBR60AN23270	6	A23 - Cement Grey		25*
CBR80AN23270	8	A23 - Cement Grey		20*
CBR100AN23270	10	A23 - Cement Grey		20*
CBR125AN23270	12,5	A23 - Cement Grey		20*
CBR150AN23270	15	A23 - Cement Grey		20*
CBR200AN23270	20	A23 - Cement Grey		20*
CBR45AN51270	4,5	A51 - Black		30*
CBR60AN51270	6	A51 - Black		25*
CBR80AN51270	8	A51 - Black		20*
CBR100AN51270	10	A51 - Black		20*
CBR125AN51270	12,5	A51 - Black		20*
CBR150AN51270	15	A51 - Black		20*
CBR200AN51270	20	A51 - Black		20*

coflex >> CBRI Spare insert Resinflex				
Item	B mm	Finish		pcs
CBRI5P23	5	P23 - Cement Grey		20*
CBRI5P51	5	P51 - Black		20*



* 10% increase for quantities lower than 20.

** 10% increase for quantities lower than those indicated.