


coflex CE

COFLEX CE is a synthetic resin movement joint designed to subdivide large tile bays. The profile size is chosen according to the tile thickness and should remain 5 +/- 1 mm below the floor elevation. The joint must be laid in correspondence with joints in the underlying substrate. Exclusively suitable for pedestrian traffic, this profile provides limited protection to the tile edges and compensates slight differential movement due to substrate contraction and expansion. Install with thin-set mortar.



CE110P10

Length: 2,70 meters



PVC
B = 8 mm



Coextruded Synthetic Resinil + Resinflex



coflex >> CE in PVC				
Item	H mm	Finish		pcs
CE70P10270	7	P10 - Transparent		100*
CE90P10270	9	P10 - Transparent		50*
CE110P10270	11	P10 - Transparent		50*
CE130P10270	13	P10 - Transparent		50*
CE150P10270	15	P10 - Transparent		50*
CE70P23270	7	P23 - Cement Grey		100*
CE90P23270	9	P23 - Cement Grey		50*
CE110P23270	11	P23 - Cement Grey		50*
CE130P23270	13	P23 - Cement Grey		50*
CE150P23270	15	P23 - Cement Grey		50*



* 10% increase for quantities lower than 20.

** 10% increase for quantities lower than those indicated.