


coflex CTR

This is a metal expansion joint with grindable insert, very resistant to the passage of loads. Ideal for ceramic tiles. The sturdy continuous metal corners protect the edges of the tiles, marble or stone and reduce mechanical stress, which in the presence of intense traffic risks compromising the integrity of the flooring. The metal side parts consist of a trimtec-type profile with a rounded upper edge and shearing to absorb high loads and tensions that affect the flooring making a single body with the thin-set mortar and the tiles. The expansion zone in EPDM has excellent hardness with the right compromise between flexibility and strength. The height of the joint to be used must be chosen in correspondence with that of the flooring to be used and the quantity of thin set used for laying, the profile must in no case protrude from the flooring surface but must be less than approx. $0.5 \div 1$ mm.



CTR100IL23

Length: 2,70 meters



**Stainless Steel + EPDM
polishable insert**

B = 9,5 mm

IL23 = IL + P23

IL51 = IL + P51

Stainless Steel + EPDM polishable insert



IL



P23



P51

**coflex >> CTR in Stainless Steel AISI 304 - DIN. 1.4301 - Polished +
Insert EPDM**

Item	H mm	Finish	pcs
CTR30IL23270	3	IL23 - Cement Grey	15**
CTR45IL23270	4,5	IL23 - Cement Grey	15**
CTR60IL23270	6	IL23 - Cement Grey	15**
CTR80IL23270	8	IL23 - Cement Grey	15**
CTR100IL23270	10	IL23 - Cement Grey	15**
CTR125IL23270	12,5	IL23 - Cement Grey	10**
CTR150IL23270	15	IL23 - Cement Grey	10**
CTR200IL23270	20	IL23 - Cement Grey	10**
CTR30IL51270	3	IL51 - Black	15**
CTR45IL51270	4,5	IL51 - Black	15**
CTR60IL51270	6	IL51 - Black	15**
CTR80IL51270	8	IL51 - Black	15**
CTR100IL51270	10	IL51 - Black	15**
CTR125IL51270	12,5	IL51 - Black	10**
CTR150IL51270	15	IL51 - Black	10**
CTR200IL51270	20	IL51 - Black	10**



* 10% increase for quantities lower than 20.

** 10% increase for quantities lower than those indicated.