


covertec EP

The COVERTEC EP profile joins two adjacent flooring surfaces (for example: concrete/ceramic tile, wood/ceramic tile and other resin or vinyl floor combinations). The overlapping section allows differential movement of the flooring, hides edging imperfections and prevents chipping and cracking. Available in aluminum and brass with patented dovetail anchoring.




EP800L


Length: 2,70 meters





Stainless Steel
B = 10 mm



Brass
B = 10 mm



Aluminum
B = 7,5 mm



* 10% increase for quantities lower than 20.

** 10% increase for quantities lower than those indicated.

Stainless Steel



IL

covertec >> EP in Stainless Steel AISI 304 - DIN 1.4301 Polished

Item	H mm	Finish		pcs
EP80IL270	8	IL - Polished		30*
EP100IL270	10	IL - Polished		30*
EP125IL270	12,5	IL - Polished		20*

Aluminum



AS



AT



EP60AT

covertec >> EP in Anodized Aluminum

Item	H mm	Finish		pcs
EP60AS270	6	AS - Silver		30*
EP60AT270	6	AT - Titan		30*

Brass



OL



ON

covertec >> EP in Natural Brass

Item	H mm	Finish		pcs
EP80ON270	8	ON - Natural		20*
EP100ON270	10	ON - Natural		20*
EP125ON270	12,5	ON - Natural		20*

covertec >> EP in Polished Brass

Item	H mm	Finish		pcs
EP80OL270	8	OL - Polished		10**
EP100OL270	10	OL - Polished		10**
EP125OL270	12,5	OL - Polished		10**

* 10% increase for quantities lower than 20.

** 10% increase for quantities lower than those indicated.