



jointec GAS

Profiltec completes its joint range, introducing the GAS structural sliding joint. The GAS joint was conceived to be installed underneath flooring (tile, stone, etc.) and over the floor slab, differently than the GA range, which can only be installed under the slab. It is particularly suitable for commercial structures, airports, parking garages and railway stations with pedestrian and lightweight vehicle passage. The joint may be installed in the interstitial space between two sections of a building or between two building bays, according to technical specifications resulting from a structural evaluation of the building.




GAS200AN

Length: 2,70 meters



Aluminum

B variable = from 33 mm a 40 mm



Aluminum



AN

AS

jointec >> GAS in Natural Aluminum				
Item	H mm	Finish		pcs
GAS100AN270	10	AN - Natural		10**
GAS125AN270	12,5	AN - Natural		10**
GAS150AN270	15	AN - Natural		10**
GAS200AN270	20	AN - Natural		8**

jointec >> GAS in Anodized Aluminum				
Item	H mm	Finish		pcs
GAS100AS270	10	AS - Silver		10**
GAS125AS270	12,5	AS - Silver		10**
GAS150AS270	15	AS - Silver		10**
GAS200AS270	20	AS - Silver		8**



* 10% increase for quantities lower than 20.

** 10% increase for quantities lower than those indicated.