

jointec GDM

This is an aluminium body structural expansion joint with synthetic rubber insert. Designed to bear structural movements of large sized buildings or compounds of buildings. To be installed on pre-existing surfaces, also vertically, over the spaces existing between two semi-detached parts of a building of smaller entity or between different beam bays. They can connect and close these interspaces adjusting themselves upwards, downwards and even transversely, according to the shrinkage-settlement movements of the whole building, be they cyclic or permanent. Within the bay frame created with the structural joints, a further surface subdivision with a suitable pattern of movement / expansion joints should always be provided for.



GDM860AN51

Length: 4,00 meters




Aluminum + Resinprene Insert

H = 17,7 mm

AN23= AN + P23

AN51= AN + P51



Aluminum + Resinprene Insert



AN P23 P51

jointec >> GDM in Aluminum + Insert Resinprene				
Item	B mm	Finish		pcs
GDM860AN23400	86	A23 - Cement Grey		1
GDM860AN51400	86	A51 - Black		1



The joints are supplied unassembled from the rubber insert.
To order the insert with the smooth surface add the letter S after the article code. Ex: GDM860AN51S400.

Upon request the profile can be cut into two pieces measuring 2m each, with a 10% price increase.

* 10% increase for quantities lower than 20.

** 10% increase for quantities lower than those indicated.