

jointec GE - GEL

JOINTEC GE aluminum structural expansion joints are composed of twin metal profiles joined by a central synthetic rubber insert. Designed to bear loads of large scale buildings or building compounds, they can be installed in the interstitial space between two sections of a building or between two bays. This technical joint links these interspaces, moving vertically and horizontally to accommodate a building's structural and material settlement. The structural bays defined by this profile should be further subdivided with smaller scale movement / expansion joints, chosen according to the expected use and flooring type.



GE200AN23


Length: 4,00 meters

Aluminum + Resinprene Insert

GE mounts the GI370 insert:
B = 44 mm
H1 = 38 mm

Aluminum + Resinprene Insert

GEL mounts the GI470 insert:
B = 54 mm
H1 = 48 mm



Aluminum + Resinprene Insert



jointec >> GE in Aluminum + Resinprene insert + GI370				
Item	H mm	Finish		pcs
GE200AN23400	20	A23 - Cement Grey		1
GE500AN23400	50	A23 - Cement Grey		1
GE200AN51400	20	A51 - Black		1
GE500AN51400	50	A51 - Black		1



The joints are supplied unassembled from the rubber insert.
To order the insert with the smooth surface add the letter S after the article code. Ex: GE500AN51S400.

Upon request the profile can be cut into two pieces measuring 2m each, with a 10% price increase.

jointec >> GEL in Aluminum + Resinprene insert + GI470				
Item	H mm	Finish		pcs
GEL200AN23400	20	A23 - Cement Grey		1
GEL500AN23400	50	A23 - Cement Grey		1
GEL200AN51400	20	A51 - Black		1
GEL500AN51400	50	A51 - Black		1



* 10% increase for quantities lower than 20.
** 10% increase for quantities lower than those indicated.