


jointec GR - GRL

JOINTEC GRM aluminum structural expansion joints are composed of twin metal profiles that allow rotational movement between the metal flanges and the central synthetic rubber insert. Designed to bear loads of large scale buildings or building compounds, they can be installed in the interstitial space between two sections of a building or between two bays. This technical joint links these interspaces, moving three-dimensionally to accommodate a building's structural and material settlement. The structural bays defined by this profile should be further subdivided with smaller scale movement / expansion joints, chosen according to the expected use and flooring type.




GR200AN51

Length: 4,00 meters




GR mounts the GI370 insert:
B = 66,7 mm
H1 = 41,7 mm


AN23= AN + P23
AN51= AN + P51



GRL mounts the GI470 insert:
B = 76,7 mm
H1 = 51,7 mm



Aluminum + Resinprene Insert



jointec >> GR in Aluminum + Resinprene insert + GI370				
Item	H mm	Finish		pcs
GR200AN23400	20	A23 - Cement Grey		1
GR500AN23400	50	A23 - Cement Grey		1
GR700AN23400	70	A23 - Cement Grey		1
GR200AN51400	20	A51 - Black		1
GR500AN51400	50	A51 - Black		1
GR700AN51400	70	A51 - Black		1

jointec >> GRL in Aluminum + Resinprene insert + GI470				
Item	H mm	Finish		pcs
GRL200AN23400	20	A23 - Cement Grey		1
GRL500AN23400	50	A23 - Cement Grey		1
GRL700AN23400	70	A23 - Cement Grey		1
GRL200AN51400	20	A51 - Black		1
GRL500AN51400	50	A51 - Black		1
GRL700AN51400	70	A51 - Black		1



The joints are supplied unassembled from the rubber insert. To order the insert with the smooth surface add the letter S after the article code. Ex: GR500AN51S400.



Upon request the profile can be cut into two pieces measuring 2m each, with a 10% price increase.

* 10% increase for quantities lower than 20.

** 10% increase for quantities lower than those indicated.