




trimtec TR-KJ

Resilient materials are commonly used for floors and walls as well as over existing flooring. For thinner flooring materials, we recommend profiles that can be solidly anchored and provide maximum edge protection. TR and KJ family of profiles meets these needs by providing a solid base with tapered openings for mechanical fastening or to be adhered using appropriate adhesive.




TR30AS


Length: 2,70 meters




Aluminum TR 30
B = 3 mm




Aluminum TR 45
B = 3 mm



Aluminum TR 60
B = 3 mm




Aluminum



AS

AT

A65



trimtec >> TR-KJ in Anodized Aluminum - Drilled				
Item	H mm	Finish		pcs
TR30ASF270	3	AS - Silver		50
TR45ASF270	4,5	AS - Silver		50
TR60ASF270	6	AS - Silver		50
KJ30ATF270	3	AT - Titan		50
KJ45ATF270	4,5	AT - Titan		40
KJ60ATF270	6	AT - Titan		40

trimtec >> TR-KJ in embossed Powder Coated Aluminum - Drilled				
Item	H mm	Finish		pcs
KJ30A65F270	3	A65 - Embossed matt Black		50
KJ45A65F270	4,5	A65 - Embossed matt Black		40
KJ60A65F270	6	A65 - Embossed matt Black		40

* 10% increase for quantities lower than 20 (■)

** 10% increase for quantities lower than those indicated (■)