


zerotec ZLT

Resilient materials are commonly used for floors and walls as well as over existing flooring. For thinner flooring materials, we recommend profiles that can be solidly anchored and provide maximum edge protection. The ZEROTEC family of profiles meets these needs by providing a solid base with tapered openings for mechanical fastening or to be adhered using appropriate adhesive. ZLT profiles provide sloped and ADA-compliant edge protection for resilient flooring materials of different heights ranging from 0 to up to ¼" (6mm).




ZLT30A65

Length: 2,70 meters




Aluminum - ZLT30

B = 6 mm
B1 = 7 mm




Aluminum - ZLT50

B = 6 mm
B1 = 14 mm





Aluminum - ZLT60

B = 11 mm
B1 = 16 mm



Aluminum



zerotec >> ZLT in Anodized Aluminum - Drilled				
Item	H mm	Finish		pcs
ZLT30ASF270	3	AS - Silver		50
ZLT50ASF270	5	AS - Silver		40
ZLT60ASF270	6	AS - Silver		30
ZLT30ATF270	3	AT - Titan		50
ZLT50ATF270	5	AT - Titan		40
ZLT60ATF270	6	AT - Titan		30

zerotec >> ZLT in embossed Powder Coated Aluminum - Drilled				
Item	H mm	Finish		pcs
ZLT30A65F270	3	A65 - Embossed matt black		50
ZLT50A65F270	5	A65 - Embossed matt black		40
ZLT60A65F270	6	A65 - Embossed matt black		30

* 10% increase for quantities lower than 20 (■)

** 10% increase for quantities lower than those indicated (■)